





# DCK3 single phase Air conditioner contactors



Single Pole



Double Pole

Protect Excess Power to PCB

**Specifications:-**

Type	Power Supply	Rated Insulation Voltage (V)	Stipulated Thermal Current (A)	Rated Working Voltage (V)	Rated Working Current (A)	Max. Making & Breaking Current (A)
DCK3-251	240-277V	600	30	24	25	150
				120	25	
				240	25	
DCK3-302	240-277V	600	40	24	30	180
				120	30	
				240	30	

# CJX2-D1810 Three phase AC contactor

**Specifications:-**

Type	Power Supply	Conventional Thermal Current (A)	Rated Operating Current (A)		Power of Controllable Motor (KW)	
			380V	660V	380V	660V
CJX2 D1810	220-660V	32	16	10.6	7.5	9




Three Phase

For any queries mail us at : [drc@seagullcooling.com](mailto:drc@seagullcooling.com)  
 visit us as at : [www.cruiseac.com](http://www.cruiseac.com) / [www.seagullcooling.com](http://www.seagullcooling.com)  
 Mob : +91 7498017700  
 Tel : 022 2687 4048 / 47 / 46 / 45 Fax : +91 022 2687 4848

**DELITE REFRIGERATION CO.**  
 Refrigeration & Air-Conditioning Products & Accessories  
 G 2 Industry House,  
 23 B Mahal Industrial Estate,  
 Mahakali Caves Road,  
 Andheri (E), Mumbai - 400 093, India.

**AIR CONDITIONER CONTACTORS**

**DCK3 single phase Air conditioner contactors**



Single Pole



Double Pole

Protect Excess Power to PCB

**Specifications:-**

Type	Power Supply	Rated Insulation Voltage (V)	Stipulated Thermal Current (A)	Rated Working Voltage (V)	Rated Working Current (A)	Max. Making & Breaking Current (A)
DCK3-251	240-277V	600	30	24	25	150
				120	25	
				240	25	
DCK3-302	240-277V	600	40	24	30	180
				120	30	
				240	30	

**CJX2-D1810 Three phase AC contactor**

**Specifications:-**

Type	Power Supply	Conventional Thermal Current (A)	Rated Operating Current (A)		Power of Controllable Motor (KW)	
			380V	660V	380V	660V
CJX2 D1810	220-660V	32	16	10.6	7.5	9



Three Phase