

Premium Quality

Rubber Load Supporter For Air Condensing Unit



Product Code	Height	Packing	Carton Size (H x W x D)
CR-100	100mm (4")	4nos (1 Set / Box)	10.2 x 21.5 x 12.4

Specification

Material	NREPOM blended compound rubber	Hardness	75 ± 5 Shore A
Color	Black	Compression strength AT 10% Deflection	Minimum 0.80 N/mm ²
Tensile Strength	Minimum 7.0 Mpa	Maximum compression strength	Minimum 6.0 N/mm ²
Elongation	Minimum 262%	Tear strength	Minimum 16 kg/cm

Best Quality ODU STAND

Wall Mounting & Floor Standing Designs
Suitable For 1 Ton to 5 Ton Capacity
Also Available in Stainless Steel



Specifications:-

MODAL	CR - STD 102	CR - STD 104	CR - STD 108
Type	Wall Model	Wall Model	Floor Model
Length Inchtmm	20"500	24"600	20"500
Rise Material Thick	1.8 mm	1.8 mm	1.8 mm
Power Coating	Yes	Yes	Yes
Anchor Fastener	3/8" x 52, 80mm, 6 Nos	3/8" x 52, 80mm, 6 Nos	No
Bolt	30 mm - 4, 13 mm - 6	30 mm - 4, 13 mm - 6	30 mm - 4
Nut	8 mm - 10 nos	8 mm - 10 nos	8 mm - 4 nos
Washer	10 Nos	10 Nos	4 Nos
Rubber Pad	Optional	Optional	Yes
Packing Details	10 Sets	10 Sets	10 Sets
Maximum wall load	150 kg	150 kg	150 kg

For any queries mail us at : drc@seagullcooling.com
visit us as at : www.cruiseac.com / www.seagullcooling.com
Mob : +91 7498017700
Tel : 022 2687 4048 / 47 / 46 / 45 Fax : +91 022 2687 4848

DELITE REFRIGERATION CO.
Refrigeration & Air-Conditioning Products & Accessories

G 2 Industry House,
23 B Mahal Industrial Estate,
Mahakali Caves Road,
Andheri (E), Mumbai - 400 093, India.

Premium Quality

Rubber Load Supporter For Air Condensing Unit



Product Code	Height	Packing	Carton Size (H x W x D)
CR-100	100mm (4")	4nos (1 Set / Box)	10.2 x 21.5 x 12.4

Specification

Material	NREPOM blended compound rubber	Hardness	75 ± 5 Shore A
Color	Black	Compression strength AT 10% Deflection	Minimum 0.80 N/mm ²
Tensile Strength	Minimum 7.0 Mpa	Maximum compression strength	Minimum 6.0 N/mm ²
Elongation	Minimum 262%	Tear strength	Minimum 16 kg/cm

Best Quality ODU STAND

Wall Mounting & Floor Standing Designs

Suitable For 1 Ton to 5 Ton Capacity

Also Available in Stainless Steel



Specifications:-

MODAL	CR - STD 102	CR - STD 104	CR - STD 108
Type	Wall Model	Wall Model	Floor Model
Length Inchtmm	20"500	24"600	20"500
Rise Material Thick	1.8 mm	1.8 mm	1.8 mm
Powder Coating	Yes	Yes	Yes
Anchor Fastener	3/8" x 52, 80mm, 6 Nos	3/8" x 52, 80mm, 6 Nos	No
Bolt	30 mm - 4, 15 mm - 6	30 mm - 4, 15 mm - 6	30 mm - 4
Nut	8 mm - 10 nos	8 mm - 10 nos	8 mm - 4 nos
Washer	10 Nos	10 Nos	4 Nos
Rubber Pad	Optional	Optional	Yes
Packing Details	10 Sets	10 Sets	10 Sets
Maximum wall load	150 kg	150 kg	150 kg